



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-122

LIQUIDATE

Acid Drain Opener

DESCRIPTION:

- A fast and powerful sulfuric acid drain opener designed to turn solid masses into free-flowing liquids.
- Liquefies grease, hair, paper, and other organic obstructions.

ADVANTAGES:

- Fast acting - industrial strength drain opener.
- Heavier than water - gets to the source of obstruction.

AREAS OF USE:

<u>Drain size</u>	<u>Product Amount/Time</u>	<u>Flushing Recommend.</u>
Small Drains	8 oz./5 minutes	Flush 2-3 minutes
3-4 inch drain	1 qt./15 minutes	Flush 5 minutes
6~8 inch drain	1/2 gal./15 minutes	Flush 5 minutes
Septic Tanks	1 gal/500 gal. <i>cap.</i>	Pour into drain

SAFETY:

Label use directions should be followed carefully. OSHA Material Safety Data Sheet available.

CAUTION:

Keep out of reach of children. Use only with adequate eye protection. Keep hands and face away from drain when using. Always wear face shield and protective clothing when applying product. Use from the bottle only, and do not transfer contents into another container. Do not apply this product when there are other chemicals present in drain line. When flushing drain lines use cold water; never use hot water, Never use a plunger when the product is in drain lines. Keep container tightly closed when not in use. Do not add water to contents while in container as a violent reaction will occur. Do not allow to contact porcelain, enamel, aluminum or chrome. To prevent accidents, rinse empty container with water before discarding. Puncture container.

USAGE:

After pouring acid into drain line, place an inverted plastic pail or dish pan over drain opening to minimize hazard of back-flash or fuming. Allow product to stand in drain line for specified time, then flush with clear, cold water. Repeat procedure if required.