



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-173

DERUSTING COLD VAT COMPOUND

DESCRIPTION:

- The very best for hot and cold tank cleaning.
- Specifically designed for cold tank use. For degreasing, paint stripping (certain paints), de-scaling and de-rusting where heat is not available.
- Contains rust inhibitor.
- Ferrous metals only, no aluminum, tin or zinc.

DIRECTIONS FOR USE:

Make up in solution at a concentration of 16-48 oz. per gallon. Heat may be used for best results in shorter periods of time for de-rusting and paint stripping. Cold water is sufficient for most cleaning. **DO NOT USE AIR AGITATION.** Such air action will gradually weaken your tank solution. Add water as necessary to maintain the solution at constant working level in the tank. Add compound as needed. Be sure that all parts to be de-rusted are completely submerged. A plastic bristle brush may be used to loosen grime or stubborn paints. After removal from the tank, all parts should be thoroughly rinsed in hot water.

SAFETY:

Label use directions should be followed carefully, OSHA Material Safety Data Sheet available.

CAUTION:

The compound contains a high percentage of caustic soda or soda lye. Keep from contact with skin or eyes. If compound comes into contact with skin, flush immediately with plenty of cool fresh water. Neutralize with wet 3% boric acid compresses. If the burned area is extensive or severe, or if the compound or solution comes into contact with the eyes, administer first aid as above, and rush the victim to medical aid.