



H & B SUPPLY, INC.
Temple, Texas
(817) 985-2525

H & B INDUSTRIES, INC..
Temple, Texas
(214) 350-1984

TECHNICAL DATA SHEET

HB-2

Con-Tak

Low-Voltage

Instrument & Contact Cleaner

Description: HB-2 is a fast drying nonconductive, formulation leaving no residue and is safe for use on plastics, rubber, and metal. This next generation product contains no CFC's, HCFC's, or other ozone depleters. Blasting spray easily cleans oil, grease, flux, dirt, and other contaminants from contacts, printed circuit boards, switches, motors, precision instruments and more. While advanced in performance and ozone safety, tills product is **FLAMMABLE AND MUST THEREFORE BE USED ONLY ON DE-ENERGIZED COMPONENTS AND EQUIPMENT.** Always allow to dry and evacuate fumes before power is returned.

Health Hazard Data: Contains Isohexanes and isopropyl Alcohol. **EXTREMELY FLAMMABLE** Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **KEEP OUT OF REACH OF CHILDREN.**

Spill or Leakage Procedures: Don not flush to sewer. Absorb with suitable material and dispose of according to local, state and federal regulations. Aerosol cans when vented of atmospheric pressure through normal use, pose no disposal hazard.

Product Specifications:

Wt. 16oz :	11 oz fill	
USDA Category;	K2 classification	
General Appearance:	Aerosol Contact & Circuit Board Cleaner	
Color:	Clear colorless	
Odor:	Aliphatic Solvent	
pH:	N/A	
Vapor Pressure At 70°F:	80-100 psig	
Spray Pattern:	Stream	
Flammability::	<u>EXTREMELY FLAMMABLE PER</u>	
	CPSC Flame Projection Test	
NFPA Code 30B:	Level 3	020105