



**H & B SUPPLY, INC.**  
Dallas, Texas  
(214) 350-1984

**H & B INDUSTRIES, INC..**  
Temple, Texas  
(254) 985-2525

**TECHNICAL DATA SHEET**

# HB-44

## CHAIN & CABLE LUBRICANT

### DESCRIPTION:

- Penetrates deep into cables to provide constant lubrication of cores and strands.
- Prolongs chain and sprocket life by reducing friction and wear
- Is unaffected by temperature changes and forces water out of metal pores.
- Contains micron-sized black moly for penetration into metal for friction reduction on metal-to-metal applications.

### TYPICAL APPLICATIONS:

Mining and Quarry equipment	Steam shovels and Cranes
Draglines	Earth moving and trenching equipment
Furnace drive chains	Redi-mix trucks
Material loading equipment on boats, trains, trucks, forklifts, conveyors,	

### AREAS OF USE:

Factories	Sprockets
Heavy machinery	Winches
Construction Equipment	Steel Cables
Oil Rigs	Driven Machinery

**GENERAL DESCRIPTION:** Aerosol Lubricant

### PROPERTIES:

Form	Solvent Based Aerosol
Odor	Petroleum Solvent
Color	Black
Toxicity	500 ppm OSHA TLV
Wetting Ability	Saturates
Detergency	None
Biodegradability	Yes
Phosphates	None
Storage Stability	1 Year +
Cold Stability	0° F
Hash Point	Above 350° F
Flame Extension	Less than 18"
Solubility in Water	0%
Specific Gravity (H <sub>2</sub> O=1)	1.10
% Volatile by Volume	45%
Evaporation Rate (Tol=1)	None
pH	None

**SAFETY:**

Label use directions should be followed carefully. OSHA Material Safety Data Sheet available.

**DIRECTIONS:**

- Shake can well before using.
- Hold can 10 to 12 inches from surfaces to be lubricated and spray.
- Use short spray bursts for most satisfactory results.

**CAUTION:**

KEEP OUT OF REACH OF CHILDREN.

**AUTHORIZATION:** USDA-H2