



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-45

Crunch

Organic Engine Degreaser

DESCRIPTION:

- Concentrated blend of organic solvents in a gel base
- Gel base allows product to cling to vertical surfaces
- Works quickly to penetrate and emulsify tar, asphalt, grease and oil
- Spray on and wash off with water or solvent
- Safe and easy to use
- Does not contain 1.1.1 Trichloroethane, CFCs or petroleum distillates
- USDA authorized

AREAS OF USE:

Auto Dealers	Factories	Homes
Hotels	Motels	Schools
Restaurants	Warehouses	Heavy Equipment

APPLICATIONS:

Tar	Grease	Oil
Asphalt Base Roofing	Compounds	Asphalt Base Cements

GENERAL DESCRIPTION: Aerosol organic engine degreaser

Properties:

Form:	Solvent Base Aerosol
Odor:	Mild Citrus
Color:	Clear
Detergency:	Excellent
Toxicity:	350 ppm OSHA TLV
Wetting Ability:	Excellent
Storage Stability:	1 year +
Cold Stability:	0°F

Continued on Page 2

PROPERTIES CONTINUED:

Phosphates:	None
Flash Point:	150° F TCC
FLAME EXTENSION:	20 Inches
Solubility in Water:	100%
Specific Gravity:	0.90
% Volatile By Volume:	7096 pH: N/A
Propellant:	Hydrocarbon
Evaporation Rate:	Slow
Biodegradability:	Yes

DIRECTIONS FOR USE:

When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar

FOR ENGINES:

Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to sit for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.

OTHER SURFACES:

To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes, Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

SAFETY:

Avoid prolonged contact with skin and eyes. If swallowed, do not induce vomiting. Call a physician immediately. Use with adequate ventilation.

CAUTION:

Flammable. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120° F may cause bursting.