



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-595

HIGH TEMPERATURE ANTI-SEIZE LUBRICANT & SEALER

(Aerosol or 1 Lb. Brush-top Can)

DESCRIPTION:

- Protects metal parts under extreme pressures and sustained temperatures up to 2,200°F
- Acts as an excellent sealant by reducing friction and making tighter joint possible
- Effective for exhaust pipes, mufflers and tail pipe clamps, bolts, nuts, studs, valve stem guides, clutch housing, torque rod and shock absorber bushings, drive shaft splines, hose connections and fittings, U-bolts, king pin bushings, heat user valves, head and manifold gaskets and many others

ADVANTAGES:

- Non corrosive -- safe on metal or rubber
- Does not harden, separate or evaporate
- Weather and salt water resistant.
- Reduces friction and wear on rubber and metal
- Acts as a sealant
- Reduces rubber deterioration from metal-rubber contact
- Decreases seizure, corrosion, pitting, galling and thread distortion
- For use both indoors and outdoors.

AREAS OF USE:

Automotive, industrial, construction, diesel fleets, farms, boat shops and chemical industry for such areas as:

Bolts, nuts & studs
Ball joints
Gaskets
Chains & sprockets
Boiler fittings
Universal joints
Snap couplers

U-bolts
Clutch housing
Guide pins & dies
Flange bolts
Lathe centers
Brake cables
Sprocket splines

Pump gaskets
Propeller shafts
Bilge pump assemblies
Pivot pins
Power take-offs
Vibrating screens
Dead axles

GENERAL DESCRIPTION: Anti-Seize Lubricant & Sealer (Aerosol or 1 Lb. Brush-top Can)

Continued on Page 2

PROPERTIES:

Form	Aerosol / 1 #Can
Odor	Mild
Color	Silver
Toxicity	Low
Wetting Ability	Excellent
Detergency	None
Foaming	None
Biodegradability	N/A
Emulsification	NA
Phosphates	None
Storage Stability	1 yr.
Cold Stability	32° F
Corrosion Factor	None
Flash Point	N/A
Boiling Point	N/A
Vapor Pressure (mmHg)	N/A
Vapor Density (Air =1)	N/A
Solubility in Water	Not Soluble
Specific Gravity (H ₂ O = 1)	N/A
% Volatile by Volume	78.0
Evaporation Rate (B.Acet. =1)	N/A
pH	N/A
Free Acid	None

SAFETY:

Label use directions should be followed carefully. OSHA Material Safety Data Sheet available

USAGE:

Spray a light coating on part and immediately assemble

CAUTION:

Do not use around liquid oxygen. Keep out of reach of children. Observe other label precautions.

AUTHORIZATION: USDA-H2