



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-67

TACKY LUBE

Open Gear Lubricant

DESCRIPTION:

- A molybdenum base lubricant formulated not to rub off of open gears
- A heavy, black consistency that lubricates and protects even under water
- Prevents rust
- Works well under low temperature conditions

ADVANTAGES:

- Excellent lubricity
- Contains moly disulfide
- Works well at temperature extremes
- Rust proofs surfaces
- Used on all metal-to-metal contact
- Does not rub off even on large gears
- Works well even under water

AREAS OF USE:

Open gears	Shears
Draglines	Presses
Crane dipper sticks	Crushing plates
Cams	Edger roll gears
Shovels	Slipper shoes
Street sweepers	Slag car spur gears
Winches	Bevel gears
Drill rigs	Cutting bars
Asphalt rollers	Plow joints

GENERAL DESCRIPTION: Aerosol Gear Lubricant.

Continued on Page 2

PROPERTIES:

Form	Aerosol
Odor	Odor
Color	Black
Toxicity	Low
Wetting Ability	Excellent
Detergency	None
Foaming	Slight
Biodegradability	No
Emulsification	None
Phosphates	None
Storage Stability	Excess of 1 Year
Cold Stability	15°F
Corrosion Factor	None
Flash Point	Concentrate = 105°F
Boiling Point	104°F
Vapor Pressure (mmHg)	38.0
Vapor Density (Air=1)	Less than 1.0
Solubility in Water	0%
Specific Gravity (H ₂ O=1)	1.023 Free
Acid	None
% Volatile by Volume	80%

SAFETY:

Label use directions should be followed carefully. OSHA Material Safety Data Sheet available.

USAGE:

Shake can well before using. Hold can about 12-18 inches from surface to be lubricated and spray. Use short spray bursts for most satisfactory results.

CAUTION:

Keep away from all sources of ignition. Use with adequate ventilation. Observe other label precautions.

AUTHORIZATION: USDA-H2