



H & B Industries, INC
 Dallas, Texas
 (214) 350-1984

H & B Supply, INC.
 Temple, Texas
 (254) 985-2525

TECHNICAL DATA SHEET

HB-81

CRETE-SEAL

Concrete & Terrazzo Seal

DESCRIPTION:

- It is both a sealer and hardener for concrete and terrazzo floors.
- Protects terrazzo and concrete against salt deterioration on concrete sidewalks, ramps, decks, etc.
- Clear in color and will not yellow under exposure to sunlight.
- Dries in 15 minutes at normal temperatures.

ADVANTAGES:

- Clear and non-yellowing.
- Slip resistant.
- Fast drying.
- Chemical and stain resistant.
- Easy to apply.
- Penetrates & seals in one operation.
- Prevents efflorescence and "blooming".
- Will allow adhesives or paints to bond to cured surface.
- Can be applied to fresh concrete without prior etching.
- Reduces floor maintenance.
- Economical-Covers 400 sq. ft. per gallon. Weather resistant.

AREAS OF USE:

- | | |
|------------------|--------------------------|
| Warehouses | Industrial plants |
| Restaurants | Nursing homes |
| Schools | Construction contractors |
| Cement companies | Terrazzo contractors |
| Locker rooms | Recreational areas |
| Shopping centers | Health spas |

GENERAL DESCRIPTION: Concrete Sealer

PROPERTIES:

Form	Liquid
Odor	Aromatic
Toxicity	Low
Wetting Ability	N/A
Detergency	None
Foaming	None
Biodegradability	N/A
Emulsification	N/A
Phosphates	None
Storage Stability	1 year

Continued on the back...

HB-81 Crete-Seal continued.

PROPERTIES (continued)

Cold Stability	32° F
Corrosion Factor	None
Flash Point	45° F T.O.C.
Boiling Point	230° F
Vapor Pressure (mmHg)	N/A
Vapor Density (Air - 1)	N/A
Solubility in Water	Not Soluble
Specific Gravity (H=0 = 1)	0,8872
% Volatile by Volume	84%
Evaporation Rate	N/A
pH	None
Free Acid	None
Wt. per Gallon	7.4 lbs.

SAFETY:

Label use directions should be followed carefully. OSHA Material Safety Data Sheet available.

USAGE;

Apply at a spread rate of 300-400 square feet per gallon using lambs wool applicator, brush, thick nap paint roller or spray. If second coat is desired, allow first to dry tack free before application of second coat.

CAUTION:

Flammable. Keep of reach of children.