



H & B Industries, INC
Dallas, Texas
(214) 350-1984

H & B Supply, INC.
Temple, Texas
(254) 985-2525

TECHNICAL DATA SHEET

HB-810

Dry Release Teflon Lubricant & Release Agent

Description:

- Chemically inert
- Non-oily
- Fast drying lubricant and release agent
- Contains an extremely fine Teflon powder
- Features outstanding microscopic film forming properties
- More slippery than silicone.
- Provides superior friction reduction in all metal on metal, rubber on metal and metal on plastic applications.
- Effective in cold for hot application from -100°F to +500°F.

Typical Applications:

Industrial Plants
Bottling Plants
Packaging Plants
Maintenance Departments

Printing Plants
Dairies Processing Plants
Manufacturing Plants
Assembly Operations.

Areas of Use:

- Safe to use on all plastic, metals, rubber, glass, wood, and paper
- More slippery than silicone, graphite or oil.
- Can be used on hinges, rollers, fittings, production machinery, conveyors, cutters, binders, and punch presses.

| | |
|---------------------------------|-------------------------------|
| Appearance and Odor..... | Clear Liquid, Solvent Odor |
| Flash Point of Concentrate..... | 49°F(T.O.C.) |
| Flammability..... | Extremely-Flammable Spray |
| Specific Gravity..... | 0.720 |
| Propellant..... | Liquefied Petroleum Gas Spray |
| Pattern..... | Fan Spray NFPA Fire |
| Rating..... | Level 3 Aerosol |