
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. -----

PRODUCT NUMBER: HB-15
IDENTITY: Tune-UP Carburetor Cleaner
Revision Date: 02/05/05

Section I

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in
this product are listed on the TSCA inventory.) -----

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM \$
ACETONE	67-64-1	1000 PPM	750 PPM	N/A
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM	
METHYL ALCOHOL	* 67-56-1	200 PPM	250 PPM	N/A
XYLENE (XYLOL)	* 1330-20-7	100 PPM	100 PPM	N/A

Comment :

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-
TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS -----

----- 147 Specific Gravity (water=1) 0.81
Section IV: FIRE AND 70PSI Melting Point: N/A
EXPLOSION HAZARD DATA >1 Evaporation Rate: 3.5
----- 0~ (Butyl Acetate=1)
----- CLEAR SPRAY, STRONG SOLVENT SCENT

-----Flash

Point (Method Used): 53F TCC Flammable Limits: LEL:1.8 UEL: 10.0 Extinguishing Media: CO2, FOAM,
WATER, DRY CHEMICAL Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Boiling Point:

Vapor Pressure (mm Hg)

Vapor Density (AIR=1)

Solubility in Water:

Appearance and Odor:

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

