

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: HB-33

IDENTITY: Penetrating Lubricant

Revision Date: 2/5/05

Section I

Manufacturer's Name: H & B Industries, Inc.

Address: 9758 Abernathy Ave.  
Dallas, TX 75220

Telephone Numbers:

Emergency: 800-535-5053  
Information: 800-466-0855

-----  
HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: 1

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

-----

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM %
L.P.G.	68476-85-7	1000 PPM	1000 PPM	N/A
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 600+ Specific Gravity (water=1) 0.90  
Vapor Pressure (mm Hg) <.01 Melting Point: N/A  
Vapor Density (AIR=1) N/A Evaporation Rate: <.1  
Solubility in Water: 0% (Butyl Acetate=1)  
Appearance and Odor: STRAW COLORED LIQUID, MILD PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

-----  
Flash Point (Method Used): +200F TCC Flammable Limits: LEL: N/A UEL: N/A  
Extinguishing Media: CO2,  
Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. FLAMMABLE.  
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

