
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. -----

PRODUCT NUMBERHB-41

IDENTITY: Dry-Out

Revision Date: 02/05/05

-----Section
I

Manufacturer's Name: H&B Industries, Inc.
Address: 9758 Abernathy Ave.
Dallas, TX 75220

Telephone Numbers:
Emergency:
800/535/5053
Information:
800/466/0855

MIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in
this product are listed on the TSCA inventory.) -----

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM \$
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A
MINERAL SEAL OIL	64741-44-2	5 MG/M3	5 MG/M3	N/A
TETRACHLOROETHYLENE	*+ 127-18-4	25 PPM	50 PPM	N/A

Comment :

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY
RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A+ KNOWN TO THE STATE OF
CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS -----

Boiling Point:	250	Specific Gravity (water=1)	1.43
Vapor Pressure(mm Hg) Vapor	15	Melting Point:	N/A
Density(AIR=1)	1	Evaporation Rate:	1
Solubility in Water:	0~	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR SPRAY,	TYPICAL CHLORINATED SOLVENT ODOR	

Section IV: FIRE AND EXPLOSION HAZARD DATA

-----Flash
Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A Extinguishing Media: STANDARD DRY
CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: NONE
Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE
120 F MAY CAUSE BURSTING.

