

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 552
IDENTITY: SLIP-NOT

Revision Date: 10/22/2002

Section I

Manufacturer's Name: QUEST CHEMICAL CORPORATION	Telephone Numbers:
Address: 12255 FM 529	Emergency:
NORTHWOODS INDUSTRIAL PARK	800/255-3924
HOUSTON	Information:
State: TX Zip Code: 77041	713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 4 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
PETROLEUM NAPHTHA VM & P	64742-89-8	500 PPM	300 PPM	N/A	___
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	___
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	250+	Specific Gravity (water=1)	0.74
Vapor Pressure(mm Hg)	2.0	Melting Point:	N/A
Vapor Density(AIR=1)	> 1	Evaporation Rate:	<1
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: CLEAR SPRAY, PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): 65F TCC Flammable Limits: LEL:1.1 UEL: 5.0
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

