

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: HB-58
IDENTITY: Stop Brake Parts Cleaner
Section I
Revision Date: 02/05/05

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

HMIS CODES: REACTIVITY: 2 FLAMMABILITY: 4 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients
contained in this product are listed on the TSCA inventory.)

=====
Name Cas No. OSHA PEL ACGIH TLV OTHER LIM %
CARBON DIOXIDE 124-38-9 5000 PPM 5000 PPM N/A
HEPTANE 142-82-5 400 PPM 400 PPM N/A
ISOPROPYL ALCOHOL 67-63-0 400 PPM 400 PPM N/A
=====

=====
Boiling Point: 156 Specific Gravity (water=1) 0.68
Vapor Pressure (mm Hg) 124 Melting Point: N/A
=====

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Vapor Density (AIR=1) < 1 Evaporation Rate: 7.1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR WATER WHITE SPRAY, SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====
Flash Point (Method Used): <20 F TCC Flammable Limits: LEL:1.2 UEL: 7.5
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire
Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.
=====

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

=====
 Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F
 Stable: X
 Incompatibility (Materials to Avoid): NONE KNOWN
 Hazardous Decomposition or Byproducts: NONE KNOWN
 Hazardous Polymerization: May Occur: Will Not Occur: X
 Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
 Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
 Health Hazards (Acute and Chronic):
 INHALATION: DIZZINESS. INGESTION: NAUSEA. SKIN: MILD IRRITATION. MAY CAUSE
 LOCALIZED DEFATTING OF TISSUE. EYES: IRRITATION, REDDENING.
 Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
 Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. APPLY
 ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING. CONTACT
 PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER
 AND CONTACT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE
SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE
AND LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR
OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.
 Ventilation: Local Exhaust: SUFFICIENT
 Mechanical: N/A Special: N/A
 Protective Gloves: N/A

WHENEVER CHEMICALS ARE USED.

Eve Protection: SAFETY GLASSES ARE RECOMMENDED
 Other Protective Clothing or Equipment: N/A
 Work/Hygienic Practices: WASH HANDS
 AFTER USE.