

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: HB-63
IDENTITY: Rust Release with/Teflon
Revision Date: 02/05/05

Section I

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM %
ETHYL ACETATE	141-78-6	400 PPM	400 PPM	_____
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM	_____
MINERAL SEAL OIL	64741-44-2	5 MG/M3	5 MG/M3	N/A _____
PETROLEUM DISTILLATES	64742-54-7	5 MG/M3	10 MG/M3	N/A _____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A _____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point: 180 Specific Gravity (water=1) 0.8
Vapor Pressure(mm Hg) 30 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: THIN BROWN LIQUID WITH STRONG SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point (Method Used): +110F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting
Procedures: SELF CONTAINED BREATHING APPRATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 574

=====

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F Incompatibility (Materials to Avoid): MAY AFFECT CERTAIN PLASTICS

Hazardous Decomposition or Byproducts: NOE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. PROLONGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. EYES:
STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED DEFATTING.
INGESTION: MAY CAUSE NAUSEA AND/OR VOMITTING. Carcinogenicity: NTP:NO IARC
Monographs:NO OSHA Reg:Yes Signs and Symptoms of Exposure:
SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CONSULT
PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF IRRITATION
PERSISTS. SKIN: WASH WITH SOAP AND WATER. CONSULT PHYSICIAN IF IRRITATION PERSISTS.
INGESTION: CONSULT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME
ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL GUIDELINES. DO NOT REUSE EMPTY CONTAINER. DO NOT PUNCTURE OR INCINERATE
CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR
OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: N/A

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: USE ONLY IN WELL VENTILATED AREA

Ventilation: Local Exhaust: ADEQUATE

Mechanical: N/A

Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: WASH HANDS AFTER USE.