

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: HB-65
IDENTITY: Pen lube Revision Date: 02/05/05
Section I

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

-HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients
contained in this product are listed on the TSCA inventory.)

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM %, and %. Rows include HEPTANE, HYDROTREATED NAPHTH. DIST, PROPANE/N-BUTANE, and TETRACHLOROETHYLENE.

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND
COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE
STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: > 200F Specific Gravity (water=1) 0.92
Vapor Pressure(mm Hg) NE Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 0 % (Butyl Acetate=1)
Appearance and Odor: RED GREASE, Petroleum ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 200F TCC Flammable Limits: LEL:1.1 UEL: 7.5
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting
Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE
TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

