

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.=====

PRODUCT NUMBER: HB-66
IDENTITY: Dry Moly Lubricant
Revision Date: 02/05/05

Section I

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

MIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)=====

Table with 5 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM. Rows include ISOPROPYL ALCOHOL, METHYLENE CHLORIDE, and PROPANE/N-BUTANE.

Comment :
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY
RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A+ KNOWN TO THE STATE
OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Specific Gravity (water=1) 1.34
Vapor Pressure(mm Hg) N/A Melting Point: N/A
Vapor Density(AIR=1) 1 Evaporation Rate: 1
Solubility in Water: O (Butyl Acetate=1)
Appearance and Odor: CHARCOAL GRAY SPRAY, MILD SWEET ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash
Point (Method Used): NONE Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: CO2, WATER, FOG, DRY CHEMICAL, FOAM Special Fire Fighting Procedures: WEAR
SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES
ABOVE 120 F MAY CAUSE BURSTING.

=====  
Stability: Unstable: Conditions to avoid:  
          Stable: X      NONE KNOWN  
Incompatibility (Materials to Avoid): STRONG ACIDS, ALKALIES, OXIDIZERS

Hazardous Decomposition or Byproducts: NONE KNOWN

Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====  
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards (Acute and Chronic):  
INHALATION: MAY CAUSE DIZZINESS. SKIN AND EYES WILL BE IRRITATED BY  
PROLONGED CONTACT. INGESTION: NAUSEA, VOMITING, DIARRHEA.

Carcinogenicity: NTP: YES IARC Monographs: Yes OSHA Reg: YES  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: BREATHING SPRAY MIST MAY  
AGGRAVATE HEART AND LUNG CONDITIONS.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN: FLUSH  
WITH WATER AND CONTACT PHYSICIAN. INGESTION: INDUCE VOMITING AND CONTACT  
PHYSICIAN. EYES: FLUSH WITH WATER AND CONTACT PHYSICIAN. INGESTION: CONTACT  
PHYSICIAN.

=====  
Steps to be Taken in Case Material is Released or Spilled: CONTAIN SPILL AND WIPE UP

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

WITH RAG. SPILLED RESIDUE SHOULD BE ABSORBED AND PLACED IN CLOSED CONTAINER. ANY  
DRIED MATERIAL SHOULD BE REMOVED WITH SUITABLE SOLVENT WITH K.B. VALUE IN EXCESS  
OF 30.

Waste Disposal Method: RESIDUE SHOULD BE KEPT IN TIGHTLY SEALED CONTAINERS AND  
DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: KEEP AWAY FROM HEAT OR OPEN  
FLAME. STORE IN A COOL, DRY AREA.

Section VIII: CONTROL MEASURES

Other Precautions: NONE

=====  
Respiratory Protection: WELL VENT. AREA IF EXCESS. TLV LEVELS ARE REACHED  
Ventilation: Local Exhaust: RECOMMENDED  
Mechanical: N/A Special: N/A Other: N/A  
Protective Gloves: RECOMMENDED-NEOPRENE  
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED. Other  
Protective Clothing or Equipment:  
ADEQUATE TO AVOID CONTACT WITH EXPOSED AREAS OF SKIN.  
Work/Hygienic Practices: WASH HANDS AFTER USE.