

-----  
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to  
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. -----  
-----

PRODUCT NUMBER: HB-67  
IDENTITY: Tacky Lube  
Revision Date: 02/05/05  
-----

Section I  
-----

Manufacturer's Name: H&B Industries, Inc. Telephone Numbers:  
Address: 9758 Abernathy Ave. Emergency:  
Dallas, TX 75220 800/535/5053  
Information:  
800/466/0855  
-----

HMIS CODES : REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: B  
-----

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in  
this product are listed on the TSCA inventory.) -----  
-----

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM \$
HEPTANE	142-82-5	400 PPM	400 PPM	N/A
HYDROTREATED PET. OILS	64742-57-0	5MG/M3	10MG/M3	
PETROLEUM RESINS	64742-16-1	N/A	N/A	5 MG/M3
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A

  
-----

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS -----  
-----

Boiling Point:	156	Specific Gravity (water=1)	0.82
Vapor Pressure(mm Hg)	NE	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0~	(Butyl Acetate=1)	
Appearance and Odor:	BLACK ASPHALT LIKE MATERIAL, PETROLEUM SOLVENT ODOR		

  
-----

Section IV: FIRE AND EXPLOSION HAZARD DATA -----

Point(Method Used):122 F	Flammable Limits: LEL:N/A	Flash
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER	UEL: N/A	
CONTAINED BREATHING APPARATUS.	Special Fire Fighting Procedures: SELF	

  
-----

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO TEMPERATURES  
ABOVE 120 F.

Section V: REACTIVITY DATA

HB-67

Stability: Unstable: Conditions to avoid: .  
Stable: X TEMPERATURES ABOVE 120 F  
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards (Acute and Chronic):  
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY CAUSE UNCONSCIOUSNESS. EYES:  
IRRITATION AND REDDENING. SKIN: MAY CAUSE IRRITATION OR DEFATTING. INGESTION: MAY  
CAUSE NAUSEA, VOMITING, ABDOMINAL CRAMPS OR DIARRHEA. Carcinogenicity: NTP:NO  
IARC Monographs:NO OSHA Reg:NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL  
AGGRAVATE RESPIRATORY, PULMONARY OR CARDIOVASCULAR ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CONTACT  
PHYSICIAN. EYES: WASH THOROUGHLY WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF  
NEEDED. SKIN: WASH WITH SOAP AND WATER. CONSULT PHYSICIAN IN IRRITATION PERSISTS.  
INGESTION: CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME  
ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND  
LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE  
CONTAINER. WRAP AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR  
OPEN FLAME. EXPOSURES TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.  
Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A  
Ventilation: Local Exhaust: ADEQUATE  
Mechanical: N/A Special: N/A Other: N/A  
Protective Gloves: CHEMICAL RESISTANT  
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED. Other  
Protective Clothing or Equipment:  
N/A  
Work/Hygienic Practices:  
WASH HANDS AFTER USE.