
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: HB-90
IDENTITY: Slick Silicone Spray Revision Date:02/05/05

Section I

Manufacturer's Name: H & B INDUSTRIES, Inc. Telephone Numbers:
Address: 9758 Abernathy Ave. Emergency:
Dallas, TX 75220 800/535/5053
Information:
800/466/0855

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: 2

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Name	Case No.	OSHA PEL	ACGIH TLV	OTHER LIM	o
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	
TRICHLOROETHYLENE	*+ 79-01-6	50PPM	200PPM	N/A	
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN
TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS -----

-----Boiling Point: 165
Specific Gravity (water=1) 1.30
Vapor Pressure (mm Hg) 100 Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, CHLORINATED SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA -----

-----Flash Point (Method Used): NONE
Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: CO2,
Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: HB-90

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY PRODUCE PHOSGENE, CARBON MONOXIDE AND HYDROGEN CHLORIDE GASES.
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. PROLONGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
EYES: STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED DEFATTING OF SKIN_
Carcinogenicity: NTP: NO IARC Monographs: Yes OSHA Reg: NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH IMMEDIATELY WITH SOAP AND WATER AND CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT STORE OR USE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.
Ventilation: Local Exhaust: YES
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: YES
Eye Protection: GOGGLES
Other Protective Clothing or Equipment:
APRON
Work/Hygienic Practices:
N/A