

## Product Data Sheet



# HB-1150 HyGuard AW Hydraulic Oil

**ISO GRADES 22, 32, 46, 68, 100, 150 & 220**

### DESCRIPTION:

- Blended from highly refined paraffinic base stock oils and selected additives to provide an oil suitable for a wide variety of hydraulic applications
- Available in various ISO grades, all with excellent low temperature flow characteristics and high viscosity indexes
- Offers maximum performance with no gumming or hardening of seals
- Blended using base stocks which have excellent resistance to emulsification and high resistance to foaming

### COMPOSITION:

Utilizing highly refined base stocks and blended with top quality additives which include:

Oxidation inhibitors	Anti-wear agents
Corrosion inhibitors	Anti-foam agents
Rust inhibitors	Pour point depressants

### PERFORMANCE CHARACTERISTICS:

- High viscosity index
- Shows very little flow rate change regard-less of changes in temperature
- Helps to prevent loss of pressure around seals
- Prevents oxidation which can clog small orifices, tightly fitted parts and lead to corrosion of metal surfaces
- Special additives prevent rust from forming by providing a protective film on metal surfaces
- Reduces fluid operating temperatures
- Provides better overall mechanical efficiency combined with less power consumption
- Extremely inexpensive due to its long life and reduced wear and tear on parts

### USES:

- Far exceeds the anti-wear requirements for Vickers Pumps as shown in the Vickers Pump Test and also meets their requirement for a "high zinc" type anti-wear hydraulic oil
- Fully approved by Sperry-Vickers and by Denison Pump Division under both their HP-2 and HP-0 specifications
- Meets and exceed the requirements of Cincinnati Milacron

### H & B Industries, Inc.

PO Box 29838, Dallas, TX. 75229  
(214)350-1984 800-466-0855  
Web: hbind.com

### H & B Supply, Inc.

301 Crickett Lane  
Temple, TX. 76501-3419  
(254)985-2525

# Product Data Sheet

## APPLICATIONS:

Construction equipment	Drilling equipment
Mining equipment	Winches
Cranes	Draglines
Plant hydraulics	Gear boxes & bearings
Deck & cargo handling equipment	Air compressors
Logging equipment	Hydraulic platforms

## HB-1150 SPECIFICATIONS:

PROPERTY	A/W 22	A/W 32	A/W 46	A/W 68	A/W 100	A/W 150	A/W 220
Viscosity Grade	22	32	46	68	100	150	220
ASTM No-	105	150	215	315	465	700	1000
API Gravity	33.2	32.4	31.7	30.9	30.0	28.9	26.8
Lbs. per gallon	7.16	7.2	7.2	7.3	7.3	7.41	7.41
Pour Point, °F	-25	-25	-20	-20	-20	-20	-25
Flash Point, °F	360	458	500	520	530	530	405
Viscosity, Typical SUS a 100° F	94	156	205	308	486	720	1012
SUS a 210° F	40	43.6	.	53.4	64.0	72	89.7
Viscosity Index	95	95	95	95	95	95	95
ASTM Rust Test (ASTM D665.	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion (ASTM D-130)	1	1	1	1	1	1	1

**H & B Industries, Inc.**  
 PO Box 29838, Dallas, TX. 75229  
 (214)350-1984 800-466-0855  
 Web: hbind.com

**H & B Supply, Inc.**  
 301 Crickett Lane  
 Temple, TX. 76501-3419  
 (254)985-2525